


# KELIT PEX

## PEX00-2 KELIT PEX pipe insulation series 2 75x6.8

3040080

### Areas of application



Medium pipe made from cross-linked polyethylene and coloured O<sub>2</sub> diffusion layer, SDR 11. Pipe connection compatible with standard connector

Application area: PN12.5 / 20°C - PN6 / 80°C - t<sub>max</sub> 95°C

Thermal insulation: PUR foam complying with EN 253 / EN 15632, closed-cell, CFC-free

Jacket pipe: corrugated PE-LD pipe, seamlessly extruded, long-term-protected against UV radiation

# Specifications


## Technical properties

pipe weight	3,90 kg/m
pipe contents	2,96 l/m
diameter inner tube	75 mm

## Product information

casing DA	162
VPE1	1,00 LFM
VPE2	149,00 ROL
L	149
weight	3,850 KGM
text	KELIT PEX pipe insulation series 2
INTRNR	39173900
main material group	KELIT PEX
material group	PEX pipe
code	PEX00-2

da



Art. No	label	pipe contents l/m
3040080	75x6.8	2,96



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)